

Water and Sewer Notes

1. All water and sewer construction shall be in accordance with specifications and standard details of the Metro Water Services.
2. The contractor is responsible for reimbursing the metro water services the cost of inspection.
3. The contractor is to provide and maintain the construction identification sign for private development approved.
4. All connections to existing manholes shall be by coring and resilient connector method.
5. Reduced pressure backflow prevention devices (rbpb) or dual check valve will be required on all test and fill lines (jumper) needed for water main construction and must be approved by the metro water services.
6. All water meters shall be a minimum of 24" not to exceed a maximum of 28" below finished grade.
7. Pressure regulating devices will be required on the customer side of the meter when pressures exceed 100 psi.
8. Pressure regulating devices will be required on the street side of the meter when pressures exceed 150 psi.
9. After completion of the sanitary sewer, the developer is responsible for the televising of the lines prior to final acceptance. The videotaping must be coordinated with the Metro Water Services inspection section. All costs will be borne by the developer.
10. Upon completion of construction of water and/or sewer, the engineer shall provide the Metro Water Services department with a complete set of as-built plans on moist erasable mylars in reverse and in digital (\*.dwg) format. Sewer plans shall be sealed by a licensed professional engineer or a registered land surveyor and shall include actual field angles between lines, all actual service lines and tee locations, the distance of the end of the service line to property corners and lines and/or station and offset from sewer centerline to end of service line, the depth to the top of the end of the service line, and shall reflect all alignment and grade changes. Water line plans shall be sealed by a licensed professional engineer or a registered land surveyor and shall include offset distance from the roadway centerline, or property line right of way, line depth, locations of hydrants, valves, reducers, tees and pressure reducing devices where applicable, all drawings must be completed and submitted prior to acceptance of the sewers or water mains into the public system and any connections being made.
11. All water mains must be located within the paved area including all blow-off assemblies
12. Public and/or private water and sanitary sewer construction plans must be submitted and approved prior to Final SP approval. The approved construction plans must match the Final Site Plan/SP plans.
13. A Capacity Study must take place, and the required capacity reserved by confirmation of capacity fee payment prior to Final Site Plan/SP approval. Unless and until 100% of capacity charge has been paid, no water/sewer capacity is guaranteed.

Landscaping Notes

1. The landscape contractor shall coordinate all construction with the appropriate utility company and shall be responsible for and damage to utilities. The landscape contractor shall verify the exact location of all utilities and take precautions to prevent damage to the utilities.
2. All planting and mulch beds shall be sprayed with round-up (contractor's option) prior to the installation of mulch.
3. Plant materials and stumps indicated for removal shall be removed and disposed off-site by the contractor. Backfill holes with topsoil free of roots and rocks.
4. The landscape contractor shall be responsible for the fine grading of all planting areas.
5. All planting areas shall be fertilized with 12W/1000 s.f. of 10-10-10 fertilizer.
6. All planting beds shall have a minimum of 3" depth of shredded hardwood bark mulch.
7. The landscape contractor shall verify all material quantities. In the event of a discrepancy, the quantities shown on the plan will take precedence.
8. The landscape contractor shall provide the owner with written instructions on the proper care of all specified plant materials prior to final payment.
9. Existing trees to remain shall be protected from construction damage. Selectively prune dead wood.
10. All disturbed areas shall be planted with turf as indicated on the materials schedule.
11. All deciduous trees, existing and proposed shall be pruned to provide 4' minimum clear trunk unless otherwise noted.
12. The landscape contractor shall provide a one year warranty on all plant materials and replace any dead or dying material within that time period.
13. No plant materials should be substituted without authorization by Dale & Associates. Plant sizes shown are minimums required by the local municipality and materials shown have been selected specifically for this project.
14. All wire baskets shall be completely removed and disposed of, burlap should be removed or punctured in at least 5 places. Remove all twine from burlapped materials.
15. Guying is not allowed unless required by municipality or site conditions. The landscape contractor shall remove wires after a one year period.
16. No canopy tree shall be located within 15' of an overhead utility. No tree shall be located within a public utility easement. Locating plant materials within a drainage easement is acceptable, but only if installed as not to disturb existing drainage flow. In such instances, the materials shall be located no closer than 5' from the centerline of drainage.
17. Lighting plan to be coordinated with proposed planting plan. no light poles to be located in tree islands. See lighting plan for proposed light locations.

NDOT Notes

1. All work within the public right of way requires an excavation permit from NDOT.
2. Proof-rolling of all street subgrades is required in the presence of the public works inspector. Inspection of the binder course is required prior to final paving in the presence of the public works inspector. These requests are to be made 24 hours in advance.
3. Stop signs are to be 30 inch by 30 inch.
4. Street signs to have six inch white letters on a nine inch green aluminum blade, high intensity reflective.
5. All pavement marking are to be thermoplastic.
6. The Developer's final construction drawings shall comply with the regulations established by NDOT in effect at the time of the approval of the Preliminary Development Plan or Final Development Plan or Building Permit, as applicable. Final Design may vary based upon field conditions.
7. Comply with the NDOT Traffic Engineer upon the Final Plan to insure adequate sight distance is provided
8. Final constructions plans shall comply with the design regulations established by the NDOT. Final design and improvements may vary based on actual field conditions.
9. All sidewalks required per the MCSP shall meet NDOT standards and are to be within dedicated right of way
10. Final constructions plans shall comply with the design regulations established by NDOT. Final design and improvements may vary based on actual field conditions.
11. On final: Callout roadway sections, ramps, sidewalks, curb & gutter, etc. per NDOT detail standards. Dimension ROW pavement widths for clarity.
12. A private hauler will be required for waste/recycle disposal.
13. Driveway spacing and parking per Metro Code

Phasing

Project to be completed in two phases.

Erosion Control and Grading Notes

1. Expose as small an area of soil as possible on the site for no more than 15 days. Keep dust within tolerable limits by sprinkling or other acceptable means.
2. All cut/fill areas to have a minimum of 6" of topsoil cover. Areas dressed with topsoil shall receive 12 lbs. per 1000 sq. ft. of 10-10-10 fertilizer (unless otherwise specified in written specifications), 5 lbs. or more of Kentucky 31 fescue seed per 1000 sq. ft., and a straw mulch cover of 70%-80% coverage (approximately 125 lbs. per 1000 sq. ft.), unless otherwise noted within written specifications.
3. Erosion control barrier is called out on plans and is to comply with the Metropolitan stormwater management manual, volume four, section TCP-14.
4. Disturbed areas are to be graded to drain as indicated in the plan to sediment barriers during and upon the completion of construction.
5. The contractor shall be responsible for the verification and the location of any existing utilities. It shall be the responsibility of the contractor to avoid damage to all existing utilities during construction. If damage does occur to any such installation, full repair will be accomplished as per the current specification governing such work.
6. Any access routes to the site shall be based with crushed stone, ASTM #1 stone, 100' long and at least 6" thick.
7. The placing and spreading of any fill material is to be started at the lowest point and brought up in horizontal layers of 8" thickness (or as directed by the soils investigative report). Said fill material is to be free of sod, roots, frozen soils, or any other decomposable material. Said fill is to be compacted to a minimum of 95% standard proctor, or as otherwise specified by the soils report or written specifications.
8. The contractor shall notify the Metro NDOT and WATER SERVICES construction compliance division, three days prior to beginning the work.
9. The contractor shall locate and stake the layout of the site in the field for inspection by the engineer. The contractor shall check the grades and final dimensions on the ground, and report any discrepancies to the engineer immediately for a decision.
10. Surplus excavation of topsoil shall be placed on the site as approved by the owner for the purpose of future landscape use.
11. The contractor shall furnish and install all necessary temporary works for the protection of the public and employees, including warning signs and lights.
12. The contractor shall be responsible for any damage done to the premises or adjacent premises or injuries to the public during the construction caused by himself, his sub-contractors, or the carelessness of any of his employees.
13. All work is to be completed with compliance to the rules and regulations set forth by Metro Water Services and NDOT. The contractor shall give all necessary notice, obtain all permits, and pay fees required for the completion of his portion of the work. He shall also comply with all city, county and state laws and ordinance or regulations relating to portions of work which he is to perform.
14. All erosion control measures shall remain in place until site is stabilized & construction is complete.
15. Contractor to provide an area for concrete wash down and equipment fueling in accordance with metro CP-10 and CP-13, respectively. Contractor to coordinate exact location with NPDES department during the pre-construction meeting. Grading permittee to include bmp's designed to control site wastes such as discarded building materials, chemicals, litter and sanitary wastes that may cause adverse impacts to water quality. The location of and/or notes referring to said bmp's shall be shown on the EPSC plan.
16. The buffer along waterways will be an area where the surface is left in a natural state, and is not disturbed by construction activity. This is in accordance with the Stormwater Management Manual Volume 1 - Regulations.
17. Drawing is for illustration purposes to indicate the basic premise of the development, as it pertains to storm water approval / comments only. The final lot count and details of the plan shall be governed by the appropriate Storm Water regulations at the time of final application.

Specific Plan Notes


1. The purpose of this plan is preliminary SP approval for 5 multifamily residential units..
2. The maximum FAR shall be 0.8
3. The maximum ISR shall be 0.8
4. Height shall be measured from the average elevation (average of 4 most exterior corners) at the finished grade (final ground elevation) to the midpoint of the primary roof pitch (the vertical distance from eave to midpoint) or to the top of the parapet for a flat roof.
5. Rear Yard Setback 20 feet
6. Side Yard Setback 5 feet
7. Setback From McClellan Ave Street 30 feet
8. Setback From Alley Street 10 feet
9. Vehicular Access From From Alley Only
10. Parking shall meet the requirements of Chapter 17.20 of the Metro Zoning Code
11. Landscaping and tree density to meet the requirements of Chapter 17.24 of the Metro Zoning Code.
12. Any excavation, fill or disturbance of the existing ground elevation must be done in accordance with Storm Water Management Ordinance No. 78-840 & Approved by the Metropolitan Department of Water Services.
13. This Property Does Not Lie Within a Flood Hazard Area as Depicted on the Current Flood Insurance Rate Maps (FIRM) Numbers 47037CO376J dated 6/20/2024.
14. All public sidewalks are to be constructed in conformance Nashville Department of Transportation sidewalk design standards. ROW and improvements should be consistent with the MCSP requirements. Access to be reviewed upon site-plan submittal and coordination with NDOT.
15. Wheel chair accessible curb ramps, complying with applicable metro NDOT standards, shall be constructed at street crossings.
16. Size driveway culverts per the design criteria set forth by the Metro Stormwater Manual (minimum driveway culvert in Metro right of way is 18" RCP).
17. Metro Water Services shall be provided sufficient & unencumbered ingress & egress at all times in order to maintain, repair, replace & inspect any stormwater facilities within the property.

18. Minor modifications to the preliminary SP plan may be approved by the Planning Commission or its designee based upon final architectural, engineering or site design and actual site conditions. All modifications shall be consistent with the principles and further the objectives of the approved plan. Modifications shall not be permitted, except through an ordinance approved by Metro Council that increase the permitted density or floor area, add uses not otherwise permitted, eliminate specific conditions or requirements contained in the plan as adopted through this enacting ordinance, or add vehicular access points not currently present or approved.
19. For any development standards, regulations and requirements not specifically shown on the SP plan and/or included as a condition of commission or council approval, the property shall be subject to the standards, regulations and requirements of the RM15-A-NS zoning district as of the date of the applicable request or application.
20. The final site plan site plan shall depict any required public sidewalks, any required grass strip or frontage zone and the location of all existing and proposed vertical obstructions within any required sidewalk and grass strip or frontage zone. Prior to the issuance of use and occupancy permits, existing vertical obstructions shall be relocated outside of any required sidewalk. Vertical obstructions are only permitted within any required grass strip or frontage zone.
21. All development within the boundaries of this plan meet the requirements of the Americans with Disabilities Act and the Fair Housing Act.
22. The requirements of the Metro Fire Marshall's Office for emergency vehicle access and adequate water supply for fire protection must be met prior to the issuance of any building permits
23. Architectural Standards:
  - a. Building facades fronting a street shall provide a minimum of one principal entrance (doorway) and a minimum of 15% glazing.
  - b. Windows shall be vertically oriented at a ratio of 1.5: 1 or greater, except for dormers.
  - c. Building facades shall be constructed of brick, brick veneer, stone, cast stone, cementitious siding, glass, or materials substantially similar in form and function, unless otherwise approved on detailed building elevations included with the preliminary SP.
  - d. Porches, if provided, shall provide a minimum of six feet of depth.
  - e. A raised foundation of 18"- 36" is required for all residential structures.

Fire Marshall

Limited building detail, and/ or building construction information provided. Construction must meet all applicable building and fire codes. Any additional fire code or access issues will be addressed during the construction permitting process. Future development or construction may require changes to meet adopted fire and building codes.

A Preliminary SP  
Radnor Corner  
2025SP-025-001  
Being Parcels 164 and 165 on Tax Map 133-01



GENERAL PLAN CONSISTENCY NOTE

This property is located in Subarea #11 (South Nashville Community Plan) and is further defined with the policy of T4 NE (Transect 4 Urban Neighborhood Evolving). T4 Urban Neighborhood Evolving (T4-NE) areas will have higher densities and/or smaller lot sizes, with a broader range and integrated mixture of housing types, providing housing choice, than some surrounding urban neighborhoods

This property is currently zoned R7.5 yet the lots are a total of 19500 sf and sits adjacent to Commercially zoned land. The property is on a street with various building building types included attached multifamily. The proposed detached multifamily units will maintain the character of the street and provide needed affordable housing options to this energized community.

Stormwater Notes

1. This site is responsible for water quality and water quantity.
2. Design of stormwater features will be provided during the final SP process.
3. Storm sewer system on this plan is shown schematically. Final design will be provided during the final SP process and will meet the requirements of the stormwater management manual.
4. This project not will disturb more than 1 acre, therefore, a NOI will not submitted to TDEC during final SP process.
5. This drawing is for illustration purposes to indicate the basic premise of the development. The final lot count and details of the plan shall be governed by the appropriate regulations at the time of final application.
6. (Any excavation, fill, or disturbance of the existing ground elevation must be done in accordance with storm water management ordinance No. 78/840 and approved by The Metropolitan Department of Water Services.)
7. (The buffer along waterways will be an area where the surface is left in a natural state, and is not disturbed by construction activity. This is in accordance with the Stormwater Management Manual Volume 1 - Regulations.)
8. (Metro Water Services shall be provided sufficient and unencumbered access in order to maintain and repair utilities in this site.)
9. (Size driveway culverts per the design criteria set forth by the Metro Stormwater Management Manual (Minimum driveway culvert in Metro ROW is 18" RCP).

NES Notes

- 1) NES can meet with developer upon request to determine service options.
- 2) The Final SP drawing shall show any existing utilities easements on property, the utility poles on the property and the poles along ROW.
- 3) The units in this development will be served from meter/meter centers.
- 4) Any additional easements required that are not part of this parcel must be obtained by the developer or the engineer for the developer.
- 5) Postal plan is required before NES's final construction drawings can be approved.
- 6) NES follows the National Fire Protection Association rules; Refer to NFPA 70 article 450-27; and NESC Section 15 - 152.A.2 for complete rules (see NES Construction Guidelines under "Builders and Contractors" tab @ www.nespower.com).
- 7) Overhead electrical power lines are required to meet or exceed the conditions as specified in the National Electrical Safety Code as adopted by the State of Tennessee in Chapter 89, Public Acts. The existing overhead power lines are located in the public right-of-ways and will require an electrical safety clearance that must be maintained during and after construction of any buildings. The National Electrical Safety Code, 2012 edition, dictates the clearances in Rule 234 C and G to provide the minimum horizontal and vertical clearances from live conductors. The overhead line must have a horizontal clearance of 7'-6" away from the nearest conductor to allow for blow-out conditions as it is configured today. It is the developer and his contractor's responsibility to ensure that they comply with OSHA regulations for working near energized conductors. Check with OSHA regulations for meeting clearances for construction near energized conductors for additional clearance requirements. Typically OSHA clearances will exceed what is required by the NESC. Often the locations of new buildings are impacted by the inability of de-energizing the circuits to meet cost and construction schedules. Proper clearances must be maintained from not only the building envelope, but also from scaffolding and other construction equipment.
- 8) If porches or walls are allowed to be constructed beyond the minimum setback limits and into the public utility easements; then the easement will be considered reduced by that much of the easement. Such encroachments may increase the cost of electrical infrastructure to allow for reduced or limited access to equipment. NES reserves the right to enter and to erect, maintain, repair, rebuild, operate and patrol electric power overhead and underground conductors and communications circuits with all necessary equipment reasonably incident thereto including the right to clear said easement and keep the same clear of brush, timber, flammable structures, buildings, permanent structures, and fire hazards; all over, under, upon, and across the easement as granted on any plat.
- 9) Quantity and location of NES equipment to be determined by the NES Engineer after receiving final plans and electrical load information. A preliminary Exhibit 'B' design will be sent to the developer or representatives of the developer for review. Suggestions or requests to the design should be made during this review process. Any changes requiring re-design, after this document has been signed, will be at the developer's expense.
- 10) Developer's vegetation design shall meet both Metro requirements and NES Vegetation Management requirements/clearances.
- 11) NES facilities will not be allowed to sit in or to pass through retention areas including rain gardens, bio-retention, bio swales and the like. This includes primary duct between pad-mounted equipment, as well as service duct to a meter or meter center.
- 12) NES riser pole should be installed on development property.
- 13) NES needs electrical load information including any house, irrigation, compactor, or pump services.

TO APPLY FOR SERVICE:

DIGITAL COPY: Provide copy of civil site plan on a CD (no pdfs; no x-ref's in .dwg file) registered to the TN State Plane Coordinate System, North American Datum 1983 (NAD83) with NO Datum Adjustment applied. Put data in separate layers and label them for easy identification.

Developer/Engineer will provide one complete set of approved plans by Metro Planning w/ all changes from other departments (fire, storm water, public works, etc...) to NES.

Developer/Engineer to provide a proposed easement drawing for the electric, phone and CATV. .

Go to www.nespower.com click on the "BUILDERS & CONTRACTORS" tab. Next click on the "Apply for Residential Subdivision" fill out the form. Then follow the direction for sending the digital drawing and the forms.

<b>Property Information</b> 406 and 408 McClellan Avenue Metro Tax Map 133-01, Parcels 164 and 165 0.45 Total Acres Zoned RS7.5 Council District 16 Ginny Welsh	<b>Electric Service</b> Nashville Electric Service (NES) 1214 Church Street Nashville, Tennessee 37246 615.747.6807	<b>Telephone Service</b> Bellsouth 866.620.6000
<b>Civil Engineer</b> Dale & Associates (Roy Dale, PE) 518 Heather Place Nashville, Tennessee 37204 615.297.5166	<b>Gas Service</b> Nashville Gas (Piedmont) 615.734.0734	<b>Utility Location</b> Tennessee One-Call 800.351.1111
<b>Owner / Developer</b> Ayodele Adegun 408 McClellan Ave Nashville, Tennessee 37211	<b>Water Service</b> Metro Water Service 1600 2nd Avenue North Nashville, Tennessee 37208 615.862.4598	<b>Floodnote</b> This Property Does Not Lie Within a Flood Hazard Area as Depicted on the Current Flood Insurance Rate Maps (FIRM) Number 47037CO376J dated 6/20/2024.
	<b>Sewer Service</b> Metro Water Services 1600 2nd Avenue North Nashville, Tennessee 37208 615.862.4598	


SPECIFIC PLAN DEVELOPMENT SUMMARY

USE		MULTI FAMILY		
PROPERTY ZONING	CURRENT RS7.5	PROPOSED SP	SURROUNDING ZONING	RS7.5
TOTAL PROPERTY SIZE		0.45 AC		
NUMBER OF RESIDENTIAL		5 UNITS		
TOTAL BUILDING FLOOR AREA		15,600 SF		
FAR		0.80		
ISR		0.80		
STREET SETBACKS:		30 FT MCCLELLAN AND 10 FT FROM ALLEY		
SIDE YARD		5'		
REAR YARD		20'		
HEIGHT STANDARDS		T HEIGHT MEASURED TO THE EAVE SHALL NOT EXCEED 30 FEET PER FIRE ACCESS REQUIREMENT		
PARKING AND ACCESS				
RAMP LOCATION AND NUMBER		ONE ACCESS FROM ALLEY AND FROM MCCLELLAN		
REQUIRED PARKING		10 SPACES		
PARKING PROPOSED		TOTAL 10 SPACES NOT COUNTING ANY GARAGE		


NOTE: PARKING SPACES TO MEET REQUIREMENTS OF THE ZONING CODE

Sheet Schedule

C1.0 Notes & Project Standards  
C2.0 Existing Conditions  
C3.0 Proposed Overall SP Layout



REV 3/30/25  
REV 7/8/25







2025SP-025-001  
Radnor Corner SP

C1.0

Notes and Project Standards


TOTAL AREA = 0.45 ACRES



REVISIONS:

Preparation Date: 1/18/16

A Preliminary SP  
**Radnor Corner**  
Being Parcels 164 and 165 on Tax Map 133-01  
Nashville , Davidson County, Tn



REV 3/30/25  
REV 7/8/25

**Dale & Associates**  
Consulting Civil Engineering  
Land Planning & Zoning  
Surveying  
Architecture

2025SP-025-001  
Radnor Corner SP  
**C2.0**


516 Heather Place  
Nashville, Tennessee 37204  
(615) 297-5166

EROSION CONTROL & GRADING NOTES


- 1) EXPOSE AS SMALL AN AREA OF SOIL AS POSSIBLE ON THE SITE FOR NO MORE THAN 15 DAYS. KEEP DUST WITHING TOLERABLE LIMITS BY SPRINKLING OR OTHER ACCEPTABLE MEANS.
- 2) ALL CUT/FILL AREAS TO HAVE A MINIMUM OF 6" OF TOPSOIL COVER. AREAS DRESSED WITH TOPSOIL SHALL RECEIVE 12POUNDS PER 1000 SQUARE FEET OF 6-12-12 FERTILIZER (UNLESS OTHER WISE SPECIFIED IN WRITTEN SPECIFICATIONS), 5 POUNDS OR MORE OF KENTUCKY 31 FESCUE SEED PER 1000 SQUARE FEET, AND A STRAW MULCH COVER OF 70%-80% COVERAGE (APPROXIMATELY 125 POUNDS PER 1000 SQUARE FEET), UNLESS OTHERWISE NOTED WITHIN WRITTEN SPECIFICATIONS.
- 3) EROSION CONTROL BARRIER IS CALLED OUT ON PLANS AND IS TO COMPLY WITH THE METROPOLITAN STORMWATER MANAGEMENT MANUAL, VOLUME FOUR, SECTION TCP-14.
- 4) DISTURBED AREAS ARE TO BE GRADED TO DRAIN AS INDICATED IN THE PLAN TO SEDIMENT BARRIERS DURING AND UPON THE COMPLETION OF CONSTRUCTION.
- 5) THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE VERIFICATION AND THE LOCATION OF ANY EXISTING UTILITIES. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO AVOID DAMAGE TO ALL EXISTING UTILITIES DURING CONSTRUCTION. IF DAMAGE DOES OCCUR TO ANY SUCH INSTALLATION, FULL REPAIR WILL BE ACCOMPLISHED AS PER THE CURRENT SPECIFICATION GOVERNING SUCH WORK.
- 6) ANY ACCESS ROUTES TO THE SITE SHALL BE BASED WITH CRUSHED STONE, ASTM #1 STONE, 100 FEET LONG AND AT LEAST 6" THICK.
- 7) THE PLACING AND SPREADING OF ANY FILL MATERIAL IS TO BE STARTED AT THE LOWEST POINT AND BROUGHT UP IN HORIZONTAL LAYERS OF 8" THICKNESS (OR AS DIRECTED BY THE SOILS INVESTIGATIVE REPORT). SAID FILL MATERIAL IS TO BE FREE OF SOD, ROOTS, FROZEN SOILS, OR ANY OTHER DECOMPOSABLE MATERIAL. SAID FILL IS TO BE COMPACTED TO A MINIMUM OF 95% STANDARD PROCTOR, OR AS OTHERWISE SPECIFIED BY THE SOILS REPORT OR WRITTEN SPECIFICATIONS.
- 8) THE CONTRACTOR SHALL NOTIFY THE METRO DAVIDSON COUNTY DEPARTMENT OF PUBLIC WORKS CONSTRUCTION COMPLIANCE DIVISION, THREE DAYS PRIOR TO BEGINNING THE WORK.
- 9) THE CONTRACTOR SHALL LOCATE AND STAKE THE LAYOUT OF THE SITE IN THE FIELD FOR INSEPTION BY THE ENGINEER. THE CONTRACTOR SHALL CHECK THE GRADES AND FINAL DIMENSIONS ON THE GROUND, AND REPORT ANY DISCREPANCIES TO THE ENGINEER IMMEDIATELY FOR A DECISION.
- 10) SURPLUS EXCAVATION OF TOPSOIL SHALL BE PLACED ON THE SITE AS APPROVED BY THE OWNER FOR THE PURPOSE OF FUTURE LANDSCAPE USE.
- 11) THE CONTRACTOR SHALL FURNISH AND INSTALL ALL NECESSARY TEMPORARY WORKS FOR THE PROTECTION OF THE PUBLIC AND EMPLOYEES, INCLUDING WARNING SIGNS AND LIGHTS.
- 12) THE CONTRACTOR SHALL BE RESPONSIBLE FOR ANY DAMAGE DONE TO THE PREMISES OR ADJACENT PREMISES OR INIURIES TO THE PUBLIC DURING THE CONTRUCTION CAUSED BY HIMSELF, HIS SUB-CONTRACTORS, OR THE CARELESSNESS OF ANY OF HIS EMPLOYEES.
- 13) ALL WORK IS TO BE COMPLETED WITH COMPLIANCE TO THE RULES AND REGULATIONS SET FORTH BY METRO WATER SERVICES. THE CONTRACTOR SHALL GIVE ALL NECESSARY NOTICE, OBTAIN ALL PERMITS, AND PAY FEES REQUIRED FOR THE COMPLETION OF HIS PORTION OF THE WORK. HE SHALL ALSO COMPLY WITH ALL CITY, COUNTY AND STATE LAWS AND ORDINANCE OR REGULATIONS RELATING TO PORTIONS OF WORK WHICH HE IS TO PERFORM.
- 14) ALL EROSION CONTROL MEASURES SHALL REMAIN IN PLACE UNTIL SITE IS STABILIZED & CONSTRUCTION IS COMPLETE.
- 15) CONTRACTOR SHALL PROVIDE AN AREA FOR CONCRETE WASH DOWN AND EQUIPMENT FUELING IN ACCORDANCE WITH METRO CP-10 & CP-13. LOCATION TO BE COORDINATED WITH THE NPDES DEPARTMENT DURING THE PRE-CONSTRUCTION MEETING.


Note:  
This Plan was prepared using Metro GIS Data. Approximated Boundary Bearings and Dimensions are referenced to State Plane Coordinate System

Case No. 2025SP-025-001  
**Existing Conditions**







Note:  Scale 1" = 30'

This Plan was prepared using Metro GIS Data. Approximated Boundary Bearings and Dimensions are referenced to State Plane Coordinate System

### Specific Plan Notes

2. The purpose of this plan is preliminary SP approval for 5 multifamily residential units.
3. The maximum FAR shall be 0.8
4. The maximum ISR shall be 0.8
5. Height shall be measured from the average elevation (average of 4 most exterior corners) at the finished grade (final ground elevation) to the midpoint of the primary roof pitch (the vertical distance from eave to midpoint) or to the top of the parapet for a flat roof.
6. Rear Yard Setback 20 feet
7. Side Yard Setback 5 feet
8. Setback From McClellan Ave Street 30 feet
9. Setback From Alley Street 10 feet
10. Vehicular Access From Alley Only
11. Parking shall meet the requirements of Chapter 17.20 of the Metro Zoning Code
12. Landscaping and tree density to meet the requirements of Chapter 17.24 of the Metro Zoning Code.
13. Any excavation, fill or disturbance of the existing ground elevation must be done in accordance with Storm Water Management Ordinance No. 78-840 & Approved by the Metropolitan Department of Water Services.
14. This Property Does Not Lie Within a Flood Hazard Area as Depicted on the Current Flood Insurance Rate Maps (FIRM) Numbers 47037CO376J dated 6/20/2024.
15. All public sidewalks are to be constructed in conformance Nashville Department of Transportation sidewalk design standards. ROW and improvements should be consistent with the MCSP requirements. Access to be reviewed upon site-plan submittal and coordination with NDOT.
16. Wheel chair accessible curb ramps, complying with applicable metro NDOT standards, shall be constructed at street crossings.
17. Size driveway culverts per the design criteria set forth by the Metro Stormwater Manual (minimum driveway culvert in Metro right of way is 18" RCP).
18. Metro Water Services shall be provided sufficient & unencumbered ingress & egress at all times in order to maintain, repair, replace & inspect any stormwater facilities within the property.
19. Minor modifications to the preliminary SP plan may be approved by the Planning Commission or its designee based upon final architectural, engineering or site design and actual site conditions. All modifications shall be consistent with the principles and further the objectives of the approved plan. Modifications shall not be permitted, except through an ordinance approved by Metro Council that increase the permitted density or floor area, add uses not otherwise permitted, eliminate specific conditions or requirements contained in the plan as adopted through this enacting ordinance, or add vehicular access points not currently present or approved.
20. For any development standards, regulations and requirements not specifically shown on the SP plan and/or included as a condition of commission or council approval, the property shall be subject to the standards, regulations and requirements of the RM15-A-NS zoning district as of the date of the applicable request or application.
21. The final site plan site plan shall depict any required public sidewalks, any required grass strip or frontage zone and the location of all existing and proposed vertical obstructions within any required sidewalk and grass strip or frontage zone. Prior to the issuance of use and occupancy permits, existing vertical obstructions shall be relocated outside of any required sidewalk. Vertical obstructions are only permitted within any required grass strip or frontage zone.
22. All development within the boundaries of this plan meet the requirements of the Americans with Disabilities Act and the Fair Housing Act.
23. The requirements of the Metro Fire Marshall's Office for emergency vehicle access and adequate water supply for fire protection must be met prior to the issuance of any building permits
24. Architectural Standards:
  - a. Building facades fronting a street shall provide a minimum of one principal entrance (doorway) and a minimum of 15% glazing.
  - b. Windows shall be vertically oriented at a ratio of 1.5:1 or greater, except for dormers.
  - c. Building facades shall be constructed of brick, brick veneer, stone, cast stone, cementitious siding, glass, or materials substantially similar in form and function, unless otherwise approved on detailed building elevations included with the preliminary SP.
  - d. Porches, if provided, shall provide a minimum of six feet of depth.
  - e. A raised foundation of 18"- 36" is required for all residential structures.

SPECIFIC PLAN DEVELOPMENT SUMMARY	
USE	MULTI FAMILY
PROPERTY ZONING	CURRENT RS7.5      PROPOSED SP      SURROUNDING ZONING RS7.5
TOTAL PROPERTY SIZE	0.45 AC
NUMBER OF RESIDENTIAL	5 UNITS
TOTAL BUILDING FLOOR AREA	15,600 SF
FAR	0.80
ISR	0.80
STREET SETBACKS:	30 FT MCCLELLAN AND 10 FT FROM ALLEY
SIDE YARD	5'
REAR YARD	20'
HEIGHT STANDARDS    T HEIGHT MEASURED TO THE EAVE SHALL NOT EXCEED 30 FEET PER FIRE ACCESS REQUIREMENT	
<b>PARKING AND ACCESS</b>	
RAMP LOCATION AND NUMBER	ONE ACCESS FROM ALLEY AND FROM MCCLELLAN
REQUIRED PARKING	10 SPACES
PARKING PROPOSED	TOTAL 10 SPACES NOT COUNTING ANY GARAGE
NOTE: TO MEET REQUIREMENTS OF THE ZONING CODE	

STORMWATER NOTES

- 1) THIS SITE IS RESPONSIBLE FOR WATER QUALITY AND WATER QUANTITY. TO PROVIDE THE FULL WATER QUALITY TREATMENT OF 80% TSS REMOVAL, A WATER QUANTITY/QUALITY BMP IS PROPOSED. DESIGN OF THIS FEATURE(S) WILL BE PROVIDED DURING THE FINAL SP PROCESS.
- 2) PROPOSED IMPROVEMENTS TO OCCUR ON NATURAL GRADES, CONTOURS TO REMAIN GENERALLY UNDISTURBED

Drawing is for illustration purposes to indicate the basic premise of the development, as it pertains to Stormwater approval / comments only. The final lot count and details of the plan shall be governed by the appropriate Stormwater regulations at the time of final application.

## NDOT NOTES

- 1) The developer's final construction drawings shall comply with the design regulations established by the Nashville Department of Transportation. Final Design may vary based upon field conditions.
- 2) Final SP Plans will be based upon a Boundary and Topographic Survey that will dimension and label existing right of ways, pavement widths, existing trees, utilities, power poles, water meters, and other physical features. Sidewalks if constructed shall have a 5 foot wide unobstructed path of travel.
- 3) If sidewalks are constructed they must have an ADA compliant ramp at the intersection of Keystone and Veritas.

## WATER SERVICES

- 1) Developer will be required to pay required capacity fees before Final SP/ Plat approval


<p><b>Property Information</b>  406 and 408 McClellan Avenue  Metro Tax Map 133-01, Parcels 164 and 165  0.45 Total Acres Zoned RS7.5  Council District 16 Ginny Welsch</p> <p><b>Civil Engineer</b>  Dale &amp; Associates (Roy Dale, PE)  516 Heather Place  Nashville, Tennessee 37204  615.297.5166</p> <p><b>Owner / Developer</b>  Ayodele Adewuyi  408 McClellan Ave  Nashville, Tennessee 37211</p>	<p><b>Electric Service</b>  Nashville Electric Service (NES)  1214 Church Street  Nashville, Tennessee 37246  615.747.6807</p> <p><b>Gas Service</b>  Nashville Gas (Piedmont)  615.734.0734</p> <p><b>Water Service</b>  Metro Water Service  1600 2nd Avenue North  Nashville, Tennessee 37208  615.862.4598</p> <p><b>Sewer Service</b>  Metro Water Services  1600 2nd Avenue North  Nashville, Tennessee 37208  615.862.4598</p>	<p><b>Telephone Service</b>  Bellsouth  866.620.6000</p> <p><b>Utility Location</b>  Tennessee One-Call  800.351.1111</p> <p><b>Floodnote</b>  This Property Does Not Lie Within a Flood Hazard Area as Depicted on the Current Flood Insurance Rate Maps (FIRM) Number 47037CO376J dated 6/20/2024.</p>
---	---	--

Case No. 2025SP-025-001  
Preliminary Specific Plan

**REVISIONS:**

Preparation Date: 1/18/16

**A Preliminary SP**  
**Radnor Corner**  
Being Parcels 164 and 165 on Tax Map 133-01  
Nashville, Davidson County, TN



3/4/25

REV 3/30/25

REV 7/8/25

REV 3/30/23

REV 7/8/25

Within a  
ted on the  
e Maps  
6J dated

**le & Associates**

Consulting Civil Engineering  
Land Planning & Zoning  
Landscape Architecture  
Surveying

2025SP-025-001

2025SP-025-001

Radnor Corner SP

# C3.0

516 Heather Place  
Nashville, Tennessee 37204  
(615) 297-5166